



Maximum Recommended Dripline Length* (m) on Flat Terrain

0-Tif

Emitter Spacing (m)	Brown 2.0 lph				Black 4.0 lph			
	Pipe Diameter O.D./I.D (mm)				Pipe Diameter O.D./I.D (mm)			
	12/9.8	16/13.6	17.8/15.2	20/17.4	12/9.8	16/13.6	17.8/15.2	20/17.4
0.2	21	40	55	74	13	27	35	47
0.3	30	60	76	100	19	39	48	63
0.5	46	89	111	144	24	56	70	92
0.8	66	125	154	199	42	78	98	126
1.0	78	146	180	231	49	92	114	147
1.2	89	166	200	266	56	104	128	166

Emitter Spacing (m)	Green 7.7 lph				Violet 16.7 lph			
	Pipe Diameter O.D./I.D (mm)				Pipe Diameter O.D./I.D (mm)			
	12/9.8	16/13.6	17.8/15.2	20/17.4	12/9.8	16/13.6	17.8/15.2	20/17.4
1.0	32	60	74	96	17	34	42	55
1.5	42	80	98	125	23	45	56	72
2.0	52	96	118	150	28	54	68	86
2.5	60	113	139	175	33	60	78	100
3.0	69	126	153	196	36	69	87	111
4.0	80	152	184	232	43	82	99	125
5.0	95	175	210	270	51	94	113	145
6.0	102	198	240	300	55	106	129	161

* Flow variation: ± 5%