

TORNADO - RAY JET

Black Nozzle - 25 lph

Maximum No. of Emitters per Lateral

(Max. Flow Rate Variation - 7.5% or 10%)

Emitter Spacing (m)	Slope (%)	Pipe Diameter in mm (OD/ID)									
		16/13.2		16/13.6		17.8/15.2		20/17		20/17.4	
		7.5%	10%	7.5%	10%	7.5%	10%	7.5%	10%	7.5%	10%
2	-2	20	22	21	23	24	28	29	33	30	34
	-1	21	23	22	25	26	30	32	36	33	37
	0	22	24	23	26	28	32	34	38	36	40
	1	23	26	24	27	30	33	37	41	39	43
	2	24	26	25	28	32	35	39	43	41	45
2.5	-2	18	20	19	21	22	25	26	30	27	31
	-1	19	21	20	22	24	27	29	33	30	34
	0	20	23	21	24	26	29	32	35	33	37
	1	21	24	23	25	28	31	34	38	36	40
	2	22	25	24	26	29	32	37	40	38	42
3	-2	16	19	17	20	20	23	24	27	24	28
	-1	17	20	18	21	22	25	26	30	27	31
	0	19	21	20	22	24	27	30	33	31	34
	1	20	22	21	23	26	29	32	36	34	37
	2	21	23	22	25	28	30	35	38	36	40
3.5	-2	15	17	16	18	19	22	22	25	22	26
	-1	16	19	17	20	21	23	25	28	26	29
	0	18	20	19	21	23	26	28	31	29	33
	1	19	21	20	22	25	27	31	34	32	35
	2	20	22	21	23	27	29	33	36	35	38
4	-2	14	16	15	17	17	20	20	24	21	24
	-1	15	18	16	18	19	22	23	27	24	28
	0	17	19	18	20	22	24	27	30	28	31
	1	18	20	19	21	24	26	30	32	31	34
	2	19	21	20	22	25	28	32	35	33	36
4.5	-2	13	15	14	16	16	19	19	22	19	23
	-1	15	17	15	18	18	21	22	25	23	26
	0	16	18	17	19	21	23	25	28	26	30
	1	17	19	18	20	23	25	28	31	30	33
	2	19	20	20	22	25	27	31	34	32	35

(-) Uphill

(+) Downhill

(Continued from page 9)

TORNADO - RAY JET
Black Nozzle - 25 lph

Emitter Spacing (m)	Slope (%)	Pipe Diameter in mm (OD/ID)									
		16/13.2		16/13.6		17.8/15.2		20/17		20/17.4	
		7.5%	10%	7.5%	10%	7.5%	10%	7.5%	10%	7.5%	10%
5	-2	13	15	13	15	15	18	18	21	18	22
	-1	14	16	15	17	18	20	21	24	22	25
	0	15	17	16	18	20	22	24	27	25	28
	1	17	19	18	20	22	24	28	30	29	32
	2	18	20	19	21	24	26	30	33	31	34
5.5	-2	12	14	13	15	15	17	17	20	17	21
	-1	13	15	14	16	17	19	20	23	21	24
	0	15	17	16	18	19	22	24	26	25	27
	1	16	18	17	19	21	24	27	29	28	31
	2	17	19	19	20	23	25	29	32	31	33
6	-2	12	13	12	14	14	16	16	19	16	20
	-1	13	15	14	15	16	19	19	22	20	23
	0	14	16	15	17	19	21	23	25	24	27
	1	16	17	17	18	21	23	26	29	27	30
	2	17	19	18	20	23	25	29	31	30	33
6.5	-2	11	13	11	13	13	16	15	18	16	19
	-1	12	14	13	15	16	18	18	21	19	22
	0	14	16	15	16	18	20	22	25	23	26
	1	15	17	16	18	20	22	25	28	27	29
	2	17	18	18	19	22	24	28	30	29	32

(-) Uphill

(+) Downhill

TORNADO - RAY JET

Blue Nozzle - 34 lph

Maximum No. of Emitters per Lateral

(Max. Flow Rate Variation - 7.5% or 10%)

Emitter Spacing (m)	Slope (%)	Pipe Diameter in mm (OD/ID)									
		16/13.2		16/13.6		17.8/15.2		20/17		20/17.4	
		7.5%	10%	7.5%	10%	7.5%	10%	7.5%	10%	7.5%	10%
2	-2	16	18	16	19	20	23	23	27	24	28
	-1	16	19	17	20	21	24	25	29	26	30
	0	17	19	18	20	22	25	27	31	28	32
	1	18	20	19	21	24	26	29	32	30	34
	2	19	21	20	22	25	27	31	34	32	35
2.5	-2	14	16	15	17	18	20	21	24	22	25
	-1	15	17	16	18	19	22	23	26	24	27
	0	16	18	17	19	21	23	25	28	26	29
	1	17	19	18	20	22	24	27	30	28	31
	2	17	19	19	20	23	25	29	32	30	33
3	-2	13	15	14	16	16	19	19	22	20	23
	-1	14	16	15	17	18	20	21	24	22	25
	0	15	17	16	18	19	21	23	26	24	27
	1	16	17	17	18	21	23	25	28	27	29
	2	16	18	17	19	22	24	27	30	28	31
3.5	-2	12	14	13	15	15	17	18	21	18	21
	-1	13	15	14	16	17	19	20	23	21	24
	0	14	16	15	17	18	20	22	25	23	26
	1	15	16	16	17	19	22	24	27	25	28
	2	16	17	17	18	21	23	26	28	27	30
4	-2	11	13	12	14	14	16	17	19	17	20
	-1	12	14	13	15	16	18	19	21	19	22
	0	13	15	14	16	17	19	21	24	22	25
	1	14	16	15	17	19	21	23	26	24	27
	2	15	16	16	18	20	22	25	27	26	29
4.5	-2	11	12	11	13	13	15	16	18	16	19
	-1	12	13	12	14	15	17	18	20	18	21
	0	13	14	13	15	16	18	20	23	21	23
	1	14	15	14	16	18	20	22	25	23	26
	2	14	16	15	17	19	21	24	26	25	28

(-) Uphill

(+) Downhill

(Continued from page 11)

TORNADO - RAY JET

Blue Nozzle - 34 lph

Emitter Spacing (m)	Slope (%)	Pipe Diameter in mm (OD/ID)									
		16/13.2		16/13.6		17.8/15.2		20/17		20/17.4	
		7.5%	10%	7.5%	10%	7.5%	10%	7.5%	10%	7.5%	10%
5	-2	10	12	11	12	13	15	15	17	15	18
	-1	11	13	12	13	14	16	17	19	17	20
	0	12	14	13	14	16	18	19	22	20	23
	1	13	15	14	15	17	19	22	24	23	25
	2	14	15	15	16	19	20	23	25	25	27
5.5	-2	10	11	10	12	12	14	14	16	14	17
	-1	11	12	11	13	13	15	16	19	17	19
	0	12	13	12	14	15	17	19	21	19	22
	1	13	14	13	15	17	19	21	23	22	24
	2	14	15	14	16	18	20	23	25	24	26
6	-2	9	11	10	11	11	13	13	16	14	16
	-1	10	12	11	12	13	15	15	18	16	18
	0	11	13	12	13	15	16	18	20	19	21
	1	12	14	13	14	16	18	20	22	21	23
	2	13	14	14	15	18	19	22	24	23	25
6.5	-2	9	10	9	11	11	13	13	15	13	15
	-1	10	11	10	12	12	14	15	17	15	18
	0	11	12	12	13	14	16	17	20	18	20
	1	12	13	13	14	16	18	20	22	21	23
	2	13	14	14	15	17	19	22	24	23	25

(-) Uphill

(+) Downhill

TORNADO - RAY JET

Green Nozzle - 55 lph

Maximum No. of Emitters per Lateral

(Max. Flow Rate Variation - 7.5% or 10%)

Emitter Spacing (m)	Slope (%)	Pipe Diameter in mm (OD/ID)									
		16/13.2		16/13.6		17.8/15.2		20/17		20/17.4	
		7.5%	10%	7.5%	10%	7.5%	10%	7.5%	10%	7.5%	10%
2	-2	12	14	13	15	16	18	19	21	20	22
	-1	13	14	13	15	16	18	20	22	21	23
	0	13	15	14	15	17	19	21	23	22	24
	1	14	15	14	16	18	19	22	24	23	25
	2	14	15	15	16	18	20	23	25	24	26
2.5	-2	11	13	12	13	14	16	17	19	18	20
	-1	12	13	12	14	15	17	18	20	19	21
	0	12	13	13	14	16	17	19	21	20	22
	1	12	14	13	15	16	18	20	22	21	23
	2	13	14	14	15	17	19	21	23	22	24
3	-2	10	12	11	12	13	15	16	18	16	18
	-1	11	12	11	13	14	15	17	19	17	19
	0	11	12	12	13	15	16	18	20	19	21
	1	12	13	12	14	15	17	19	21	20	22
	2	12	13	13	14	16	17	20	22	21	23
3.5	-2	10	11	10	11	12	14	15	16	15	17
	-1	10	11	11	12	13	14	16	18	16	18
	0	11	12	11	12	14	15	17	19	18	19
	1	11	12	12	13	14	16	18	20	19	21
	2	11	13	12	13	15	17	19	21	20	22
4	-2	9	10	10	11	11	13	14	15	14	16
	-1	10	11	10	11	12	14	15	17	15	17
	0	10	11	11	12	13	14	16	18	17	18
	1	10	12	11	12	14	15	17	19	18	20
	2	11	12	12	13	14	16	18	20	19	21
4.5	-2	9	10	9	10	11	12	13	15	13	15
	-1	9	10	10	11	12	13	14	16	15	16
	0	10	11	10	11	12	14	15	17	16	18
	1	10	11	11	12	13	15	16	18	17	19
	2	10	11	11	12	14	15	17	19	18	20

(-) Uphill

(+) Downhill

(Continued from page 13)

TORNADO - RAY JET

Green Nozzle - **55** lph

Emitter Spacing (m)	Slope (%)	Pipe Diameter in mm (OD/ID)									
		16/13.2		16/13.6		17.8/15.2		20/17		20/17.4	
		7.5%	10%	7.5%	10%	7.5%	10%	7.5%	10%	7.5%	10%
5	-2	8	9	9	10	10	12	12	14	13	14
	-1	9	10	9	10	11	12	13	15	14	16
	0	9	10	10	11	12	13	15	16	15	17
	1	10	11	10	11	13	14	16	17	17	18
	2	10	11	11	12	13	15	17	18	18	19
5.5	-2	8	9	8	9	10	11	12	13	12	14
	-1	8	9	9	10	11	12	13	14	13	15
	0	9	10	9	10	11	13	14	16	15	16
	1	9	10	10	11	12	14	15	17	16	18
	2	10	11	10	11	13	14	16	18	17	19
6	-2	7	8	8	9	9	11	11	13	12	13
	-1	8	9	8	9	10	11	12	14	13	14
	0	8	9	9	10	11	12	14	15	14	16
	1	9	10	10	11	12	13	15	16	16	17
	2	10	10	10	11	13	14	16	17	17	18
6.5	-2	7	8	8	9	9	10	11	12	11	13
	-1	8	9	8	9	10	11	12	13	12	14
	0	8	9	9	10	11	12	13	15	14	15
	1	9	10	9	10	12	13	15	16	15	17
	2	9	10	10	11	12	13	16	17	16	18

(-) Uphill

(+) Downhill

TORNADO - RAY JET

Red Nozzle - 70 lph

Maximum No. of Emitters per Lateral

(Max. Flow Rate Variation - 7.5% or 10%)

Emitter Spacing (m)	Slope (%)	Pipe Diameter in mm (OD/ID)									
		16/13.2		16/13.6		17.8/15.2		20/17		20/17.4	
		7.5%	10%	7.5%	10%	7.5%	10%	7.5%	10%	7.5%	10%
2	-2	11	13	12	14	15	17	18	20	18	21
	-1	12	13	12	14	15	17	18	21	19	22
	0	12	14	13	14	16	18	19	21	20	22
	1	12	14	13	15	16	18	20	22	21	23
	2	13	14	13	15	17	18	21	23	22	24
2.5	-2	10	12	11	12	13	15	16	18	17	19
	-1	11	12	11	13	14	16	17	19	18	20
	0	11	12	12	13	14	16	18	20	18	21
	1	11	13	12	13	15	17	18	20	19	21
	2	12	13	12	14	15	17	19	21	20	22
3	-2	10	11	10	12	12	14	15	17	15	18
	-1	10	11	11	12	13	14	16	18	16	18
	0	10	12	11	12	13	15	16	18	17	19
	1	11	12	11	13	14	15	17	19	18	20
	2	11	12	12	13	14	16	18	20	19	21
3.5	-2	9	10	10	11	12	13	14	16	14	16
	-1	9	11	10	11	12	14	15	17	15	17
	0	10	11	10	11	13	14	16	17	16	18
	1	10	11	11	12	13	15	16	18	17	19
	2	10	11	11	12	14	15	17	19	18	20
4	-2	9	10	9	10	11	12	13	15	14	15
	-1	9	10	9	11	11	13	14	16	14	16
	0	9	10	10	11	12	13	15	16	15	17
	1	10	11	10	11	13	14	16	17	16	18
	2	10	11	10	12	13	14	16	18	17	19
4.5	-2	8	9	9	10	10	12	12	14	13	15
	-1	8	9	9	10	11	12	13	15	14	16
	0	9	10	9	10	11	13	14	16	15	16
	1	9	10	10	11	12	13	15	17	16	17
	2	9	10	10	11	13	14	16	17	16	18

(Continued from page 15)

TORNADO - RAY JET
Red Nozzle - 70 lph

Emitter Spacing (m)	Slope (%)	Pipe Diameter in mm (OD/ID)									
		16/13.2		16/13.6		17.8/15.2		20/17		20/17.4	
		7.5%	10%	7.5%	10%	7.5%	10%	7.5%	10%	7.5%	10%
5	-2	8	9	8	9	10	11	12	13	12	14
	-1	8	9	8	10	10	12	13	14	13	15
	0	8	9	9	10	11	12	14	15	14	16
	1	9	10	9	10	12	13	14	16	15	17
	2	9	10	10	11	12	13	15	17	16	17
5.5	-2	7	8	8	9	9	11	11	13	12	13
	-1	8	9	8	9	10	11	12	14	13	14
	0	8	9	9	10	11	12	13	15	14	15
	1	8	9	9	10	11	12	14	15	15	16
	2	9	10	9	10	12	13	15	16	15	17
6	-2	7	8	7	9	9	10	11	12	11	13
	-1	7	8	8	9	10	11	12	13	12	14
	0	8	9	8	9	10	11	13	14	13	15
	1	8	9	9	10	11	12	13	15	14	16
	2	9	9	9	10	11	13	14	16	15	16
6.5	-2	7	8	7	8	9	10	10	12	11	12
	-1	7	8	8	9	9	10	11	13	12	13
	0	8	8	8	9	10	11	12	14	13	14
	1	8	9	8	9	11	12	13	15	14	15
	2	8	9	9	10	11	12	14	15	15	16

(-) Uphill

(+) Downhill