

Tafftif - Performance curves Flow rate Vs. Pressure

Date : 3.8.2001

Tafftif Drippers name	Nominal FR (l/h) (In accordance with ISO)	Color Code	Cat No.
Tafftif 2.0 barb	2.1	Brown	32100002
Tafftif 2.0 threaded	2.1	Brown	32120002
Tafftif 4.0 barb	4.1	Black	32100004
Tafftif 4.0 threaded	4.1	Black	32120004
Tafftif 8.0 barb	8	Green	32100008
Tafftif 12.0 barb	11.3	Red	32100012

Working pressure range : 0.8-2.5 bar

Installation : Use 2mm punch tool

26/03/2002

	Color Code			
	Brown	Black	Green	Red
	Flow rate (l/h)			
Pressure (m)	2	4	8	12
2	0.9	1.9	3.8	5.8
4	1.30	2.60	5.20	7.70
6	1.60	3.20	6.30	9.10
8	1.90	3.70	7.20	10.30
10	2.10	4.10	8.00	11.30
12	2.30	4.50	8.70	12.10
14	2.60	4.80	9.30	12.90
16	2.70	5.10	9.90	13.70
18	2.90	5.40	10.50	14.40
20	3.10	5.70	11.00	15.00
25	3.50	6.40	12.20	16.50

Taffif - Performance curves Flow rate Vs. Pressure

