

Maximum Recommended Dripline Length* (m) on Flat Terrain



Tufftif

Emitter Spacing (m)	Brown 2..1 lph		
	Pipe Diameter O.D./I.D (mm)		
	16/13.6	17.8/15.2	20/17.4
0.2	50	61	77
0.3	65	79	100
0.4	78	95	120
0.5	90	110	138
0.6	101	123	155
0.8	122	147	186
1.0	140	170	215
1.2	157	191	241
1.5	174	213	273

Emitter Spacing (m)	Black 4.1 lph		
	Pipe Diameter O.D./I.D (mm)		
	16/13.6	17.8/15.2	20/17.4
0.2	34	41	52
0.3	44	54	68
0.4	53	64	81
0.5	61	74	94
0.6	68	83	105
0.8	82	100	126
1.0	95	115	145
1.2	107	130	163
1.5	117	144	185

Emitter Spacing (m)	Green 8.0 lph		
	Pipe Diameter O.D./I.D (mm)		
	16/13.6	17.8/15.2	20/17.4
0.2	23	28	35
0.3	29	36	45
0.4	35	43	54
0.5	41	49	63
0.6	46	55	70
0.8	54	66	84
1.0	63	76	97
1.2	71	85	108
1.5	78	96	123

Emitter Spacing (m)	Red 11.3 lph		
	Pipe Diameter O.D./I.D (mm)		
	16/13.6	17.8/15.2	20/17.4
0.2	19	23	29
0.3	24	30	38
0.4	29	36	45
0.5	34	41	52
0.6	38	46	58
0.8	46	55	70
1.0	52	64	80
1.2	59	71	90
1.5	65	80	102

* Flow variation: ± 5%